

CEL632A Occupational Sound Level Meter



Features

- Data Logging with detailed Time History store
- Voice Notes and Audio Recording
- Automatic On/Off Timers
- Measures Lavg, TWA, Leq, Lepd, Min, Max, etc. Simultaneously
- Range: 20 to 140 dB(A)
- Back Erase to remove unwanted noise events
- Data Markers

Applications

- Occupational Noise Measurements
- Hearing Protector Checks
- OSHA, MSHA, ACGIH, European and other occupational noise regulations

Overview

In addition to the usual measurements needed for an occupational noise assessment, the CEL632 has advanced automatic timing and detailed storage features.

The CEL632A Sound Level Meter measures all the parameters needed for a successful survey of workplace noise. The main parameters - Lavg, Leq, Peak, Lmax, Fast, Slow, etc. - are all measured simultaneously, so there is no need to choose before starting the measurement. With a single span from 20 to 140dB, there is also no need to choose the measurement range either.

Data Logging and Software

The CEL632A comes complete with data logging capability with measurements stored in the meter's large internal memory.

CasellaDrive

When connected to a Windows computer using the free CasellaDrive software, the meter acts like a memory stick (shows as a removable drive) so the measurements can be loaded into a spreadsheet or moved to your hard drive for long term storage. There is no need to buy special software.

Insight

Due to the large amount of data and the potential complexity of the measurements, we would recommend the use of the Insight software. It simplifies the process of downloading the measurements and stores them in a database, managed by person, place or process criteria. The Insight software is included with the sound level meter.

CEL632A Occupational Sound Level Meter

Specifications

Specifications

The CEL632A data logging Integrating Sound Level Meter is available as either Type 1 or Type 2 as defined by the international sound level meter standards.

Measurement range	20 to 140 dB (single range), 143 dB Peak
Display	320 x 240 pixel color TFT
Output to PC	USB Mini B
Batteries	3 x AA Alkaline (15 hours with backlight off)
External Power	9 to 14V DC at 250mA (2.1mm connector)
Dimensions	72 x 229 x 31mm, 295g 2.8" x 9.0" x 1.2". 10.4oz
Memory	1GB >2.5 years when logging set to 1 second
Timers	Duration 1s to 24h On/Off Timers: 6 sets with selectable times and repeat function.
Audio Recording	8kHz sampling, 60 hours recording 24kHz sampling, 10 hours recording

Sound Level Meter Standards

- ANSI S1.4 and ANSI S1.43 Type 1 or Type 2
- IEC 60651 and IEC 60804 Type 1 or Type 2
- IEC 61672 Class 1 or Class 2

Using a meter that meets these standards is essential for repeatable results and especially for any measurements that will be used for legal purposes.

Measured Parameters

Frequency weightings	A, C and Z (simultaneous)
Time weightings	Fast, Slow and Impulse
Amplitude weightings	Q3, Q4 and Q5
Thresholds	70 to 90 dB (applies to Lavg)
Sound Level	LXY, LXYMax, LXYMin, LC- LA
Integrated Peak	LXeq, Lavg, LAE LXPeak
Takt Max	LTM3, LTM5, LXleq
Time History Level 1	Periods of 1 minute to 1 hour
Time History Level 2	Periods of 1 second to 30 mins

Where X is frequency weighting A, C or Z and Y is time weighting Fast, Slow or Impulse

Head Office

NoiseMeters Ltd
7 Jayes Park
Ockley
Surrey
RH5 5RR

Telephone **+44 130 677 0855**
Fax **+44 845 680 0316**

Email: **info@noisemeters.com**
Support: **support@noisemeters.com**

Web Sites

Main site:
<https://au.noisemeters.com>

Product shortcut:
<https://au.noisemeters.com/p/cel632a2/>

Tech Support:
<https://support.noisemeters.com>